An Automated Method for Depicting Mesocyclone Paths and Intensities

Madison L. Miller¹

Cooperative Institute of Mesoscale Meteorological Studies, University of
Oklahoma and National Severe Storms Laboratory, Norman, Oklahoma

Valliappa Lakshmanan

Cooperative Institute of Mesoscale Meteorological Studies, University of
Oklahoma and National Severe Storms Laboratory, Norman, Oklahoma

Travis M. Smith

Cooperative Institute of Mesoscale Meteorological Studies, University of
Oklahoma and National Severe Storms Laboratory, Norman, Oklahoma

Accepted by Weather and Forecasting, Nov. 2012

¹*Corresponding author address:* Madison L. Miller, School of Meteorology, University of Oklahoma, 120
David L. Boren Blvd., Norman, OK 73072.
E-mail: madison.burnett@noaa.gov

Abstract

The location and intensity of mesocyclone circulations can be tracked in real-time by accumulating azimuthal shear values over time at every location of a uniform spatial grid. Azimuthal shear at low (0-3 km AGL) and mid levels (3-6 km AGL) of the atmosphere is computed in a noise-tolerant manner by fitting the Doppler velocity observations in the neighborhood of a pulse volume to a plane and finding the slope of that plane. Rotation tracks created in this manner are contaminated by non-meteorological signatures caused by poor velocity dealiasing, ground clutter, radar test patterns and spurious shear values. In order to improve the quality of these fields for real-time use and for an accumulated multi-year climatology, new dealiasing strategies, data thresholding, and Multiple Hypothesis Tracking (MHT) techniques have been implemented. These techniques remove nearly all non-meteorological contaminants resulting in much clearer rotation tracks that appear to match mesocyclone paths and intensities closely.

1. Introduction

a. Motivation

To depict the paths and intensities of mesocyclone circulations as seen by radar, the National Severe Storms Laboratory (NSSL) creates products called “rotation tracks”. These rotation track fields are created by calculating the azimuthal shear fields (the azimuthal derivative of radial velocity) for each radar, merging the azimuthal shear data from multiple radars onto Cartesian grids and then accumulating the maximum values in those gridded fields over time onto one accumulated grid. An example is shown in Figure 1.

These tracks can help alleviate some of the difficulty in interpreting and analyzing velocity fields. They can provide information about the spatial extent and strength of mesocyclone signatures over time and can be quite useful for conducting poststorm damage surveys. The American Red Cross of Central Oklahoma uses NSSL rotation track products plotted on maps to determine where to deliver assistance after tornado events and the best routes to get there. After the 24 May 2011 tornado outbreak in Central Oklahoma, the use of rotation tracks helped to significantly reduce the disaster assessment time (NOAA/NSSL 2011). These fields are also useful in real-time as guidance for forecasters and have enormous data mining potential. However, they are plagued by non-meteorological signatures caused by poor velocity dealiasing, ground clutter, radar test patterns, and spurious shear values. As seen in Figure 2, these artifacts can make the tracks difficult, if not impossible, to interpret meaningfully.

One of the goals of the Multi-Year Reanalysis of Remotely Sensed Storms (MYRORSS) project, a cooperative effort between National Oceanic and Atmospheric

Administration's (NOAA) NSSL and the National Climatic Data Center (NCDC), is to create a CONUS-wide climatology of low and mid level rotation track fields for the lifetime of the Weather Surveillance Radar 1988-Doppler (WSR-88D) network.

Cintineo et al. (2011) developed an automated system to process Level-II radar data (Crum and Alberty 1993) at NSSL using a multiple-machine framework and the Warning Decision Support System – Integrated Information (WDSS-II; Lakshmanan et al. 2007b) suite of programs to process and quality control the data. A preliminary hail climatology using Maximum Estimated Size of Hail (MESH) grids was also created. Here, we extend the processing to velocity-based products, specifically to azimuthal shear accumulations.

The CONUS-wide rotation track climatology will provide an incredibly rich dataset with numerous potential climatological and severe weather applications. Track lengths, intensities, and other characteristics could be analyzed by geographical region and time of year. Potential relationships could also be discovered between rotation tracks and environmental parameters like convective available potential energy (CAPE) and storm-relative helicity (SRH). After correlating maximum azimuthal shear and maximum updraft helicity, rotation tracks could also be used as verification for high-resolution model-simulated maximum updraft helicity tracks like the ones discussed by Kain et al. (2010) and Clark et al. (2012).

The purpose of this paper is to discuss the special velocity dealiasing techniques, data thresholds, and Multiple Hypothesis Tracking (MHT) techniques developed to isolate the rotation tracks in real-time and for the MYRORSS climatology. Detailed

explanations of each quality control effort will be given and the specific impacts of each step will be shown in example cases.

b. Background

Modern Doppler radars have the ability to provide high resolution space and time measurements of storms that allow for the detection of mesocyclone-scale circulations. Couplets in radial velocity fields as well as hook echo signatures in reflectivity fields have been used to identify these circulations in the past, but methods of identifying mesocyclone or tornado circulations reliant solely on hook echo signatures have proven unreliable (Forbes 1981; Mitchell et al. 1998). Methods using radial velocity signatures such as the Tornado Detection Algorithm (TDA; Mitchell et. al 1998) and the NSSL Mesocyclone Detection Algorithm (MDA; Stumpf et. al 1998) have been more successful.

The TDA currently used with the WSR-88D system relies on high “gate-to-gate velocity difference” values to identify potentially tornadic circulations (Mitchell et al. 1998). Although termed a tornado detector, the algorithm identifies tornadic vortex signatures (which may or may not be associated with tornadoes) that are typically larger than a tornado owing to radar sampling resolution (e.g., Brown et al. 1978). The gate-to-gate difference represents the difference between velocity values at constant range from the radar between adjacent azimuths. These values can be affected adversely by the azimuthal offset of the radar beam center from the vortex, noisy data, and velocity aliasing (Wood and Brown 1997). Additionally, because the radar beam is much broader at far ranges than when near the radar, observed velocity peaks within vortices decrease in magnitude, allowing some vortices to be overlooked by the algorithm.

Liu et al. (2007) proposed a wavelet analysis technique to help mitigate these issues. The method examines region-to-region radial wind shears at a number of different spatial scales to more accurately determine the amount of shear present, reducing the number of false tornado detections.

Rather than using the gate-to-gate velocity difference, “peak-to-peak” methods of calculating rotational shear from Doppler radial velocity data or the wavelet analysis technique to detect a vortex, a two-dimensional, *local, linear least squares derivatives (LLSD) method* can be used to reduce the impact of noise. Elmore et al. (1994) proposed this method of estimating the derivatives of radial velocity values by fitting a plane to the velocity field and finding its slope. The vertical vorticity field is estimated by the azimuthal derivative of the radial velocity field and is given by

$$\frac{\partial V_r}{\partial s} = \frac{\sum s_{ij} V_{ij} \omega_{ij}}{\sum (\Delta s_{ij})^2 \omega_{ij}} \quad (1)$$

where V_r is the radial velocity, s is the coordinate in the azimuthal direction, s_{ij} is the arc length from the center point of the calculation to the point (i, j) , V_{ij} is the radial velocity at point (i, j) , and Δs_{ij} is the beam width at a given range. ω_{ij} is a positive weight function that we set to 1 after determining that Cressman weight functions, among others, generated very little differences. The coordinate i is in the radial direction and j is in the azimuthal direction. The summation is performed over range gates in the neighborhood of the starting point of the calculation. This calculation of azimuthal shear is, here on, referred to as the LLSD method.

Smith and Elmore (2004) applied the LLSD calculation to simulated and observed circulations by first passing the velocity data through a 3x3 median filter (Lakshmanan

2012) to reduce speckle noise and then applying Eq.1 to the filtered velocity data to estimate the azimuthal shear. The physical size of the neighborhood used in the calculation is held constant such that fewer radials are used in the calculation at far ranges from the radar. Typical sizes of radial and azimuthal neighborhoods are 750 m and 2500 m, respectively.

The LLSD calculation helps to remove some of the dependence on radar location involved in rotation detection and also allows circulation signatures to be viewed in three-dimensional space or as input to multi-sensor applications. It was shown by Smith and Elmore (2004) that LLSD shear values were reasonable estimations of actual shear values in simulated Rankine vortices when sampled by a theoretical WSR-88D radar (Brown et al. 2002) out to a range of ~140 km. The variance of these values was also much smaller compared to peak-to-peak shear.

The use of the median filter in the LLSD shear technique can be a disadvantage, however. Whereas areas with large velocity gradients are preserved, this filter can also smooth out peaks in the velocity field. Although the median filter is beneficial when these peaks are associated with noisy data, the filter decreases the magnitude of peak velocities in mesocyclone signatures and completely eliminates tornado signatures in nearly all cases. For this reason, LLSD shear values may underestimate the actual azimuthal shear of circulations, especially for small circulations (Mitchell and Elmore 1998).

Defining a neighborhood size in the LLSD technique also forces a trade-off between spatial resolution and noise resistance. Smaller neighborhoods are more strongly affected by noise, whereas larger neighborhoods tend to underestimate actual shear

values of circulations. The spatial scale of the LLSD calculation makes it most useful for detecting large mesocyclone-scale circulations, however, the increased noise resistance makes identification of small circulations more difficult.

Rotation tracks help to visualize the movement of mesocyclone circulations (or occasionally circulations associated with nearby large tornadoes) over time as seen by radar. To produce these tracks, radial velocity data are first dealiased using the default WSR-88D dealiasing algorithm (Eilts and Smith 1990). Next, a quality control neural network (Lakshmanan et al. 2007a) is used to remove echoes in the reflectivity field produced by biological targets, anomalous propagation, ground clutter, and test or interference patterns. The algorithm successfully removes nearly all non-meteorological signatures from the Reflectivity fields examined.

This quality controlled reflectivity field, hereafter ReflectivityQC, and the radial velocity field are then employed by the shear estimation algorithm of Smith and Elmore (2004) to compute the azimuthal shear (see Fig. 3). Two-dimensional maximum azimuthal shear fields within low (0-3 km) and mid (3-6 km) level layers above ground level (AGL) are also calculated using digital elevation model (DEM) data to determine the height of each point above the ground.

These single-radar 2-D maximum azimuthal shear fields are then merged into a Cartesian multi-radar grid using the intelligent agent formulation of Lakshmanan et al. (2006), accounting for varying radar beam geometry with range, vertical gaps between radar scans, and other issues. The maximum value of each pixel in the merged multi-radar grid over a time interval (typically 60 -120 minutes) is then used to produce the swaths of merged maximum azimuthal shear known as rotation tracks. Missing data in

the rotation track fields (denoted by “MD” in the color bar) corresponds to any data below the signal to noise threshold for the radar. Ideally, this should be shown as zero shear, not missing data. Figure 4 provides a flow chart showing the algorithms and fields used to create rotation tracks.

2. Methods

a. Two-dimensional velocity dealiasing

Due to the relationship between radar wave length (λ) and the pulse repetition frequency (F), a radar correctly measures the radial velocity given that it is in the range of $\pm V_N$, where

$$V_N = \frac{\lambda F}{4}. \quad (2)$$

Here, V_N is the Nyquist velocity and the true velocity is

$$V = V_m \pm 2nV_N \quad (3)$$

where V_m is the measured velocity, n is an unknown integer including zero, and V_m must satisfy $-V_N \leq V_m \leq V_N$. Velocity dealiasing is the process of determining the correct value of n to successfully recover V . In the cases when V cannot be successfully recovered, the velocity is still aliased and can usually be identified in radial velocity fields by abrupt changes in values between neighboring measurements. Most first generation dealiasing algorithms (e.g. Ray and Ziegler 1977, Barga and Brown 1980) were one-dimensional and detected abrupt changes between single radials. For this reason, they were quite sensitive to noisy, incorrect data. Strong shear zones in these radial velocity fields sometimes cannot be dealiased without data from multiple

208 dimensions. Merritt (1984), Boren et al. (1986), and Bergen and Albers (1988) took more
209 sophisticated approaches and used velocity data in two dimensions to dealias. These
210 methods were costly in terms of computation time, however.

211 The local environment dealiasing (LED) algorithm (Eilts and Smith 1990) is the
212 method currently used for WSR-88D data in real-time. The scheme applies radial
213 continuity constraints to remove local aliasing errors and azimuthal continuity checks to
214 mitigate error. It also incorporates radial averages to determine n (see Eq. 3) when
215 continuity thresholds are not met. Each radial is processed individually and compared
216 against the previously dealiased radials, allowing the algorithm to use less memory and
217 process faster than other two-dimensional algorithms. It can also ingest a vertical wind
218 profile from an environmental sounding to produce initial values for each elevation scan
219 and for isolated echoes. It is an efficient algorithm that begins by using simple checks and
220 only moves on to more sophisticated techniques if needed. This approach performed very
221 well on the cases of severe aliasing presented in Eilts and Smith (1990), but performed
222 poorly when qualitatively examined in many of the tornadic cases examined for this
223 study. Ingesting the vertical wind field from a 20-km Rapid Update Cycle model (RUC;
224 Benjamin et al. 2004) point sounding at each radar site to use as an environmental
225 estimate into the LED algorithm improved the dealiasing to some extent.

226 For this study, a sophisticated two-dimensional dealiasing technique described by
227 Jing and Wiener (1993) was implemented. The algorithm solves a linear system of
228 equations that minimizes gate-to-gate shear in each isolated two-dimensional region.
229 Through using aliasing-induced discontinuity information, the correction values for all
230 gates are found by solving a two-dimensional least-mean-squares problem. Instead of

making dealiasing decisions for each gate based on its neighbors, which can be subject to scattered incorrect data, this approach avoids local expansion of errors by attempting to find all dealiased values for a given dataset. Vertical profiles of horizontal wind data from the 20-km RUC point soundings were used as environmental wind estimates at the grid-point nearest to each radar site. The calculated average is minimized by incrementing n equally over the entire echo. The average local wind observed by radar is assumed to be less than V_n .

A smooth environmental wind field with weak shear is assumed. This can be a poor assumption in isolated areas of strong wind shear associated with mesocyclones or microbursts. In these cases, relatively short falsely aliased border segments are detected and can typically be used to dealias the field correctly. In more elongated regions of shear associated with strong gust fronts, for example, incorrect dealiasing is more likely. Example dealiased radial velocity fields and their corresponding azimuthal shear fields using both the LED and Jing and Weiner (1993) methods are shown in Fig. 3. Preliminary results from a study now underway to determine which velocity dealiasing method performs best on a set of case studies indicate that this two-dimensional technique is more accurate than the LED technique.

b. Reflectivity quality control

As mentioned in the introduction, the quality control neural network (Lakshmanan et al. 2007b, Lakshmanan et al. 2010) is used to remove non-meteorological echoes from the reflectivity field. The algorithm combines various measures from both past literature (e.g. Steiner and Smith 2002, Kessinger et al. 2003, Fulton et al. 1998) and new measures to discriminate between precipitating and

nonprecipitating echoes in the reflectivity data. A region-by-region classification is performed rather than a gate-by-gate basis. In addition, clear air echoes due to biological contamination are identified and removed using a two-stage intelligent machine algorithm while retaining echoes that correspond to precipitation (Lakshmanan et al. 2010).

c. Additions to LLSD shear algorithm

In addition to calculating the azimuthal shear fields as described earlier in this paper, extra operations have been added to the LLSD algorithm. These additions are discussed in the following sections.

1) AZIMUTHAL SHEAR RANGE CORRECTION

A new azimuthal shear range-correction (Newman et al. 2012) algorithm is applied to the field in an effort to correct for range degradation due to radar beam widening. A multiple linear regression technique was used to create the equations based on comparisons between observed shear values and those computed using simulated Rankine vortices. First, the algorithm identifies significant circulations using reflectivity and LLSD shear criteria. To avoid applying the range-correction to regions of noise in the shear fields co-located with low reflectivity values, only circulations in regions with reflectivity values greater than 20 dBZ and LLSD shear values exceeding 0.005 s^{-1} are identified. The peak-to-peak velocity differences and shear diameters of circulations satisfying the reflectivity and shear criteria are calculated next. A median filter is applied to the shear diameter field to provide potentially more accurate estimates of circulation size when circulations are larger than tornadic vortex signatures (TVSs; Brown, Lemon,

and Burgess 1978). Then, new azimuthal shear values for each pixel in the circulations are calculated by inserting the associated shear diameter, maximum velocity measured, and range values into the appropriate regression equations. Newman et al. (2012) found that the algorithm increased tornadic shear values appropriately and aided in the differentiation between tornadic and nontornadic scans.

2) DATA THRESHOLDS AND REMOVAL

Significant vertical shear near the surface can cause false high azimuthal shear values very close to the radar. To prevent these high values from corrupting the multi-year climatology, azimuthal shear values within a 5-km radius of each radar site are set to ‘missing’. While this will remove some ‘good’ data, it will also remove a great deal of anomalously high azimuthal shear values that could corrupt the climatology. An example is shown in Figure 5. This near-radar data removal is not applied to the rotation tracks in this paper, nor will it be used in generation of rotation tracks in real-time. It is used only in the climatology to avoid accumulations at areas where the azimuthal shear values are known to be poor.

When processing the two-dimensional maximum azimuthal shear fields, all shear data not co-located with a given ReflectivityQC value are removed so that only shear data associated with storm regions are retained. In order to retain meteorologically significant shear data in low reflectivity hook echo regions, a 5x5 dilation filter (Lakshmanan 2012) is applied to the ReflectivityQC field. This operation assigns the maximum reflectivity value in a 5x5 moving window to each pixel, effectively expanding the areas of high reflectivity values. The threshold operation is then performed on the dilated ReflectivityQC field to help remove azimuthal shear associated with interference

patterns, anomalous propagation, and other radar-related issues not successfully removed by the radar reflectivity quality control neural network. Setting this threshold at 40 dBZ retained the meteorological rotation signatures in the azimuthal shear fields while removing a great deal of shear co-located with non-meteorological signatures (see Figure 6).

d. Creation of rotation tracks

To better isolate the rotation tracks in the accumulated grid, new quality control strategies have been implemented on the input two-dimensional maximum azimuthal shear fields for both low and mid levels of the atmosphere. Clusters of high azimuthal shear values in each time step are tested and removed if their sizes and/or data value distributions are not indicative of meteorological phenomena. If these remaining clusters in each time step are associated with lasting circulations, they make it into the final rotation track products.

1) HYSTERESIS SEGMENTATION

Before the circulation signatures in the two-dimensional maximum azimuthal shear fields can be associated between time steps, they are isolated into *clusters* of high shear values using hysteresis segmentation. The term hysteresis (Jain 1989) refers to the lag observed between the application of an electromagnetic field and its subsequent effect on a substance. In image processing, the term refers to the lagging effect caused by using two thresholds – one to begin the thresholding process and another to end it. In this application, two data thresholds are maintained and a cluster is composed of contiguous pixels with values greater than the lower data threshold that contains at least one pixel

with a data value greater than the higher threshold. The higher threshold identifies areas of high azimuthal shear associated with strong circulation and the lower hysteresis threshold grows the region around the high value to include all pixels associated with the circulation (see Figure 7). Through experimentation on numerous tornadic and nontornadic case studies, it was determined that low and high data thresholds of 0.002 s^{-1} and 0.005 s^{-1} , respectively, and a minimum size of 25 pixels performed well for isolating clusters of high azimuthal shear.

All pixels in the maximum 2-D azimuthal shear layer fields not associated with identified clusters are then removed so that only the azimuthal shear clusters are accumulated over time to produce rotation tracks. This eliminates the low background azimuthal shear values not associated with circulations, making the tracks themselves more isolated, as seen in Figure 8.

2) MULTIPLE HYPOTHESIS TRACKING

Typically, clusters of high azimuthal shear values associated with mesocyclones persist through many time steps, whereas clusters associated with remaining non-meteorological signatures typically only appear sporadically. To isolate the meteorological rotation tracks, these non-meteorological shear clusters need to be removed from the accumulated fields. Multiple Hypothesis Tracking (MHT) (Cox and Hingorani 1996) techniques are used to isolate the continuous tracks of azimuthal shear clusters associated with storms and remove the short-lived non-meteorological azimuthal shear clusters.

MHT techniques have been used in the fields of video processing and military target tracking for years and recently have been adopted by the meteorology community

(e.g. Root et al. 2011). The technique attempts to associate objects, in this case azimuthal shear clusters, throughout time. It is innovative as it considers time associations globally and makes association decisions that can be deferred until additional information is available. If the algorithm is not certain whether an existing track should be associated with cluster A or cluster B in the current time step, for example, it can create two hypotheses (see Figure 9). Both possibilities are then propagated forward in time to when enough information should be available to determine which hypothesis most likely. The clusters that do not meet the minimum longevity threshold (two time steps or roughly 10 minutes) are then retroactively pruned so that they are not admitted into the rotation track fields.

An association cost matrix is constructed so an entry, $d_{i,j}$, indicates the cost of matching cluster i at one time step with cluster j at the next time step. Each association has a computed cost based on cluster sizes, ages, proximities to clusters from previous time steps and other characteristics. The associations with the lowest cost are made. Enumeration of all the hypothesis matrices to find the lowest costs can increase exponentially with each time step, so a technique based on Murty (1968) is used to prune the set to retain only the k-best associations at each time step. The algorithm is illustrated in Figure 10. For more details and to see quantitative improvements in simulated fields through the use of MHT, the reader is referred to Lakshmanan et al. (2012).

In an effort to remove any lingering non-meteorological clusters, a data value distribution threshold was set. It was observed that the majority of clusters associated with meteorological clusters exhibited unimodal distributions of azimuthal shear data values with central tendencies while the non-meteorological clusters typically exhibited

uniform distributions of very high azimuthal shear values (see examples in Figure 11). To account for this, clusters are pruned if more than 80% of their pixel values are greater than or equal to 0.02 s^{-1} . This has only an incremental impact on the field itself since most non-meteorological clusters are removed before this point.

Bands of high azimuthal shear values associated with linear meteorological phenomena like outflow boundaries and bow echoes also appear in the rotation track fields. In an effort to isolate the mesocyclone signatures from these bands of shear, all clusters were fit to ellipses and their aspect ratios were calculated. After testing many different thresholds, it was determined that size, data value distribution, and aspect ratio information could not be successfully used to discriminate between mesocyclone clusters and shear band clusters. Because of this, the band signatures remain in the rotation track fields for now.

3. Results

The quality control techniques discussed in the methods section were developed and tuned through testing on a variety of tornadic and nontornadic cases. The specific impacts of each technique will now be discussed and demonstrated in this section using cases that were not part of this training dataset.

a. New velocity dealiasing techniques

Prior to this study, the LED dealiasing technique (Eilts and Smith 1990), the default method used for real-time processing of WSR-88D data, was used in the creation of rotation tracks. Recently, it was found that using the vertical profile of horizontal wind from the 20-km RUC point sounding at radar sites as estimates of the environmental wind

in the algorithm helped to alleviate some of the dealiasing issues, though many still persisted.

The two-dimensional dealiasing technique described by Jing and Weiner (1993) was tested and appears to perform much better at properly dealiasing the velocity fields due to the large reduction in radial spikes and non-meteorological velocity signatures. Using the RUC wind profiles as environmental estimates made some additional improvements as well. As seen by the representative example in Figure 12, the Jing and Weiner technique dealiases correctly many of the areas that the LED technique did not. Almost all of the noisy, high azimuthal shear values associated with dealiasing issues are removed by using the Jing and Weiner technique, making the rotation tracks much easier to interpret. A quantitative study to determine the best velocity dealiasing techniques is ongoing.

b. Range correction and reflectivity thresholds

Whereas the azimuthal shear range correction does not make many visible improvements to the rotation track fields, the azimuthal shear values in storm circulations are more accurate estimates of the actual shear values. The ReflectivityQC threshold below which all co-located shear data is removed is increased from 20 dBZ to 40 dBZ. This “stamping out” of azimuthal shear by the dilated ReflectivityQC field helps to further isolate the azimuthal shear signatures associated with storms, as seen in Figure 13.

c. Hysteresis segmentation

The rotation tracks are even further isolated from any background azimuthal shear values through the use of hysteresis segmentation. The tracks are more isolated and easier

to interpret (Fig. 14) since only the azimuthal shear clusters are accumulated over time rather than the entire field, including the low background values.

d. Multiple hypothesis tracking

After using hysteresis segmentation to form azimuthal shear clusters, the MHT algorithm is used to isolate the persistent clusters associated with storm-scale circulations from the non-meteorological clusters associated with any remaining poor velocity dealiasing signatures. Figure 15 illustrates the removal of some small, leftover circulations from the 27 April 2011 case by the MHT algorithm.

Figure 16 illustrates the differences between the original rotation track fields and the rotation track fields after the quality control efforts were implemented on four recent tornadic cases. Due to space constraints, only the overall improvements are shown. Radial spikes, which were especially problematic in the 16 April 2011 case over Virginia and North Carolina, were successfully removed. The low background azimuthal shear values and nearly all azimuthal shear values not associated with storms are removed in all four cases. Broad areas of non-mesocyclone shear still exist near some radar sites, but overall a significant improvement is seen in the quality of the data and the ease of interpretation.

To get a more quantitative idea of how MHT impacts rotation track fields, a cluster-tracking algorithm described in Lakshmanan et al. (2003) was used to identify and track the number of clusters in the 24 May 2011 event before and after implementing MHT. Before MHT was implemented, 62 different clusters were identified and tracked, whereas after MHT, only 41 clusters were identified and tracked in the eight hour case. The low level rotation tracks associated with these post-MHT clusters compare well to

reported tornado tracks in the several cases visually examined. Figure 17 shows how the low level rotation track products associated with tornado damage paths from the 24 May 2011 event across central Oklahoma compare to the EF-scale ratings.

4. Conclusion

NSSL rotation track products are valuable tools in disaster response situations. They allow users to quickly assess both the spatial extent of mesocyclone circulations as seen by radar over time and assess their relative intensities. While these products were useful, a great deal of contamination initially was present due to poor velocity dealiasing, ground clutter, radar test patterns and spurious shear values. These non-meteorological signatures made the tracks nearly impossible to see in some extreme cases.

To mitigate these problems for both real-time use and for a multi-year rotation track climatology as part of the MYRORSS project, quality control strategies were developed and implemented. A two-dimensional velocity dealiasing technique using 20-km RUC wind data as input made large visual improvements in the quality of the initial radial velocity field. An azimuthal shear range correction algorithm and some simple data thresholds were added to the LLSD shear algorithm. Hysteresis segmentation was used to isolate clusters of high azimuthal shear associated with mesocyclone circulations in each time step of the two-dimensional maximum azimuthal shear fields and MHT techniques were used to associate them throughout time. Any clusters that did not persist for at least 10 minutes (2 time steps) or were comprised of an unrealistic distribution of high azimuthal shear values were pruned. The remaining clusters were kept and used to create the rotation track fields.

While a few issues like the broad shear signatures around some radar sites remain, overall the rotation track fields show a great deal of qualitative improvement after the implementation of the quality control efforts. Whereas the tracks associated with the mesocyclones initially were diluted by background noise and non-meteorological signatures, they are now isolated and easier to interpret. Incorporating these improvements, processing of the MYRORSS rotation track climatology should begin in the near future.

Acknowledgments.

Funding for the authors was provided under NOAA-OU Cooperative Agreement NA17RJ1227. The authors thank Kiel Ortega, Kevin Manross, John Cintineo, and Jennifer Newman for all their help and advice. The authors also thank Gabe Garfield, Kiel Ortega and Brandon Smith for allowing us to use their damage survey data for the 24 May 2011 tornadoes.

References

- Bargen, D. W., and R. C. Brown, 1980: Interactive radar velocity unfolding. Preprints, *19th Conf. on Radar Meteorology*, Miami, FL, Amer. Meteor. Soc., 278–283.
- Benjamin, S. G., and Coauthors, 2004: An hourly assimilation-forecast cycle: The RUC. *Mon. Wea. Rev.*, **132**, 495–518.
- Bergen, W. R., and S. C. Albers, 1988: Two- and three-dimensional de-aliasing of Doppler radar velocities. *J. Atmos. Oceanic Technol.*, **5**, 305–319.
- Boren, T. A., J. R. Cruz, and D. S. Zrnić, 1986: An artificial intelligence approach to Doppler weather radar velocity dealiasing., *Proc. 23rd Conf. on Radar Meteorology*, Snowmass, CO, Amer. Meteor. Soc., 107–110.
- Brown, R. A., L. R. Lemon, and D. W. Burgess, 1978: Tornado detection by pulsed Doppler radar. *Mon. Wea. Rev.*, **106**, 29–38.
- Brown, R. A., V. T. Wood, and D. Sirmans, 2002: Improved tornado detection using simulated and actual WSR-88D data with enhanced resolution. *J. Atmos. Oceanic Technol.*, **19**, 1759–1771.
- Cintineo, J., T. Smith, V. Lakshmanan, and S. Ansari, 2011: An automated system for processing the Multi-Year Reanalysis of Remotely Sensed Storms (MYRORSS).

494 Preprints, *27th Conf. on Interactive Information Processing Systems (IIPS)*, Seattle, WA,
495 Amer. Meteor. Soc., J9.3.
496
497 Clark, A. J., J. S. Kain, P. T. Marsh, J. Correia, Jr., M. Xue, and F. Kong, 2012:
498 Forecasting tornado path lengths using a 3-dimensional object algorithm applied to
499 convection-allowing forecasts. *Wea. Forecasting*, In Press.
500
501 Cox, I., and S. L. Hingorani, 1996: An efficient implementation of Reid's multiple
502 hypothesis tracking algorithm and its evaluation for the purpose of visual tracking. *IEEE*
503 *Trans. Pattern Anal. Mach. Intell.*, **18**, 138-150.
504
505 Crum, T. D., and R. K. Alberty, 1993: The WSR-88D and the WSR-88D Operational
506 Support Facility. *Bull. Amer. Meteor. Soc.*, **74**, 1669-1687.
507
508 Eilts, M. D., and S. D. Smith, 1990: Efficient dealiasing of Doppler velocities using local
509 environment constraints. *J. Atmos. Oceanic Technol.*, **7**, 118–128.
510
511 Elmore, K. M., E. D. Albo, R. K. Goodrich, and D. J. Peters, 1994: NASA/NCAR
512 airborne and ground-based wind shear studies. Final Report, contract no. NCC1-155, 343
513 pp.
514
515 Forbes, G. S., 1981: On the reliability of hook echoes as tornado indicators. *Mon. Wea.*
516 *Rev.*, **109**, 1457–1466.

517

518 Fulton, R., D. Breidenback, D. Miller, and T. O'Bannon, 1998: The WSR-88D rainfall
 519 algorithm. *Wea. Forecasting*, **13**, 377-395.

520

521 Jain, A., 1989: *Fundamentals of Digital Image Processing*. Prentice Hall, 569 pp.

522

523 Jing, Z., and G. Wiener, 1993: Two-dimensional dealiasing of Doppler velocities. *J.*
 524 *Atmos. Oceanic Technol.*, **10**, 798–808.

525

526 Kain, J. S., S. R. Dembek, S. J. Weiss, J. L. Case, J. J. Levit, R. A. Sobash, 2010:
 527 Extracting unique information from high-resolution forecast models: Monitoring selected
 528 fields and phenomena every time step. *Wea. Forecasting*, **25**, 1536–1542.

529

530 Kessinger, C., S. Ellis, and J. Van Andel, 2003: The radar echo classifier: A fuzzy logic
 531 algorithm for the WSR-88D. Pre-prints, *Third Conf. on Artificial Applications to the*
 532 *Environmental Sciences*, Long Beach, CA, Amer. Meteor. Soc., CD-ROM, P1.6.

533

534 Lakshmanan, V., R. Rabin, and V. DeBrunner, 2003: Multiscale storm identification and
 535 forecast. *J. Atmos. Res.*, 367-380.

536

537 Lakshmanan, V., T. Smith, K. Hondl, G. J. Stumpf and A. Witt, 2006: A real-time, three-
 538 dimensional, rapidly updating, heterogeneous radar merger technique for reflectivity,
 539 velocity and derived products. *Wea. Forecasting*, **21**, 802-823.

540

541 Lakshmanan, V., A. Fritz, T. Smith, K. Hondl, and G. J. Stumpf, 2007a: An automated
542 technique to quality control radar reflectivity data. *J. Appl. Meteor.*, **46**, 288-305.

543

544 Lakshmanan, V., T. Smith, G. J. Stumpf, and K. Hondl, 2007b: The Warning Decision
545 Support System – Integrated Information. *Wea. Forecasting*, **22**, 596-612.

546

547 Lakshmanan, V., J. Zhang, and K. Howard, 2010: A technique to censor biological
548 echoes in radar reflectivity data. *J. Appl. Meteor.*, **49**, 35-462.

549

550 Lakshmanan, V., 2012: Neighborhood and window operations. *Automating the Analysis*
551 *of Spatial Grids: A Practical Guide to Data Mining Geospatial Images for Human &*
552 *Environmental Applications*, Springer, 129-171.

553

554 Lakshmanan, V., M. Miller, and T. Smith, 2012: Quality control of accumulated fields by
555 applying spatial and temporal constraints. *J. Atmos. Ocean. Tech.*, Accepted. [Available
556 online at <http://www.cimms.ou.edu/~lakshman/Papers/mhtqc.pdf>.]

557

558 Liu, S., M. Xue, and Q. Xu, 2007: Using wavelet analysis to detect tornadoes from
559 Doppler radar radial-velocity observations. *J. Atmos. Oceanic Technol.*, **24**, 344-359.

560

561 Merritt, M. W., 1984: Automatic velocity dealiasing for real-time applications. *Proc.*
562 *22nd Conf. on Radar Meteorology*, Zurich, Amer. Meteor. Soc., 528-533.

563 Mitchell, E. D., and K. L. Elmore, 1998: A technique for identifying regions of high
564 shear associated with mesocyclones and tornadic vortex signatures. Preprints, *14th*
565 *International Conference on Interactive Information and Processing Systems (IIPS) for*
566 *Meteorology, Oceanography, and Hydrology*, Phoenix, AZ. Amer. Meteor. Soc., 312-
567 315.

568

569 Mitchell, E. D., S. V. Vasiloff, G. J. Stumpf, A. Witt, M. D. Eilts, J. T. Johnson, K. W.
570 Thomas, 1998: The National Severe Storms Laboratory tornado detection algorithm.
571 *Wea. Forecasting*, **13**, 352–366.

572

573 Murty, K. G., 1968: An algorithm for ranking all the assignments in order of increasing
574 cost. *Operations Research*, **16**, 682-687.

575

576 Newman, J. F., V. Lakshmanan, P. L. Heinselman, M. B. Richman, and T. M. Smith,
577 2011: Range-correcting azimuthal shear in Doppler radar data. *Wea. Forecasting*, In
578 Press.

579

580 National Oceanic and Atmospheric Administration (NOAA) National Severe Storms
581 Laboratory (NSSL), cited 2011: NOAA technology helps American Red Cross respond
582 faster. [Available online at [https://secure.nssl.noaa.gov/briefings/2011/06/noaa-](https://secure.nssl.noaa.gov/briefings/2011/06/noaa-technology-helps-american-red-cross-respond-faster/)
583 [technology-helps-american-red-cross-respond-faster/](https://secure.nssl.noaa.gov/briefings/2011/06/noaa-technology-helps-american-red-cross-respond-faster/)]
584

- 585 Ray, P. S., and C. Ziegler, 1977: De-aliasing first-moment Doppler estimates. *J. Appl.*
586 *Meteor.*, **16**, 563–564.
- 587
- 588 Root, B., M. Yeary, and T.-Y. Yu, 2011: Novel storm cell tracking with multiple
589 hypothesis tracking. Preprints, *27th Conf. on Interactive Information Processing Systems*
590 *(IIPS)*, Seattle, WA, Amer. Meteor. Soc., 8B.3.
- 591
- 592 Steiner, M., and J. A. Smith, 2002: Use of three-dimensional reflectivity structure for
593 automated detection and removal of nonprecipitating echoes in radar data. *J. Atmos.*
594 *Oceanic Technol.*, **19**, 673–686.
- 595
- 596 Stumpf, G. J., A. Witt, E. D. Mitchell, P. L. Spencer, J. T. Johnson, M. D. Eilts, K. W.
597 Thomas, and D. W. Burgess, 1998: The National Severe Storms Laboratory mesocyclone
598 detection algorithm for the WSR-88D. *Wea. Forecasting*, **13**, 304–326.
- 599
- 600 Smith, T. M., and K. L. Elmore, 2004: The use of radial velocity derivatives to diagnose
601 rotation and divergence. Preprints, *11th Conf. on Aviation, Range and Aerospace*,
602 Hyannis, MA, Amer. Meteor. Soc., P5.6.
- 603
- 604 Wood, V. T., and R. A. Brown, 1997: Effects of radar sampling on single-Doppler
605 velocity signatures of mesocyclones and tornadoes. *Wea. Forecasting*, **12**, 928–938.
- 606
- 607

List of Figures

FIG. 1. Low level (0-3 km AGL) rotation tracks from the 27 April 2011 tornado outbreak. Swaths of high maximum azimuthal shear approximate the movement and strength of mesocyclone circulations within the supercells that moved southwest to northeast across the states of Alabama, Mississippi, and Tennessee between 16 UTC on 27 April and 00 UTC on 28 April.

FIG. 2. Low level (0-3 km AGL) rotation tracks across Virginia, North Carolina and South Carolina from the 16 April 2011 tornado outbreak generated using the default WSR-88D velocity dealiasing technique and without any quality control techniques. The spikes of high azimuthal shear values are caused by poor velocity dealiasing along radials and can make data interpretation difficult, if not impossible, in some areas.

FIG. 3. Radial velocity fields and the corresponding azimuthal shear fields from KDGX on 27 April 2011 at 2151 UTC created using different dealiasing strategies. (a) Radial velocity dealiased using the LED algorithm. (b) Azimuthal shear field associated with (a). (c) Radial velocity dealiased using the LED algorithm with an environmental wind field from an input 20-km RUC point sounding. (d) Azimuthal shear associated with (c). (e) Radial velocity field dealiased using the Jing and Weiner (1993) technique with an environmental wind field from an input 20-km RUC point sounding. (f) Azimuthal shear field associated with (e).

FIG. 4. Flow chart showing how rotation track products are created. Grey boxes with dashed lines represent algorithms and white boxes with solid lines represent data fields.

FIG. 5. (a) Low level (0-3 km AGL) rotation track field from the 2 March 2012 outbreak from the KVWX radar site before data removal near the radar site. Note the high values of azimuthal shear surrounding the radar site at the center of the image. (b) The same rotation track field after the removal of data within a 5-km radius of the radar site. This removal will only be performed for the climatology, not in real-time.

FIG. 6. (a) Reflectivity, (b) ReflectivityQC, (c) radial velocity, and (d) azimuthal shear fields associated with a supercell over central Alabama on 27 April 2011 at 2107 UTC.

FIG. 7. A schematic showing how hysteresis segmentation works. The first and last peaks of azimuthal shear values will be associated with clusters, while the middle peak will not be associated with a cluster because it contains no values above the higher data threshold.

FIG. 8. Low level (0-3 km AGL) rotation tracks associated with the tornadic supercells that moved across Mississippi and Alabama between 16 UTC on 27 April 2011 and 00 UTC on 28 April 2011. (a) Rotation tracks before hysteresis segmentation. (b) Rotation tracks after hysteresis segmentation is used to threshold the field.

FIG. 9. Example of how the MHT algorithm tracks clusters and generates hypotheses. Solid shapes represent the position of azimuthal shear clusters at the given time step. Solid arrows show the movement of clusters between time steps. Dotted shapes show the projected locations of the azimuthal shear clusters in the next time steps. Dashed arrows show the projected movement of the clusters between time steps. Shape A shows the projected location of the original cluster at time t . Shape B represents the actual location of the original cluster at time t . The algorithm generates two hypotheses for time $t + 1$ (C and D). If the location of B is an error, then at time $t + 1$ the cluster should move to position D. If the location of B is not an error but a change in motion, then B should move to location C at time $t + 1$. At time $t + 1$, the discovery of the target at either C or D will confirm one hypothesis and disprove the other. The disproved cluster is deleted and the confirmed one continues on to the next time step. In this case, given the strange shape and size of B, it is likely that this cluster is associated with a non-meteorological shear signature and will not persist in time $t + 1$.

FIG. 10. Multiple hypothesis tracking flow chart adapted from Root et al. (2011).

FIG. 11. An example of a cluster of high azimuthal shear values associated with a mesocyclone circulation is shown in (a) and the histogram of its data values after hysteresis segmentation is shown in (b). An example of a cluster of high azimuthal shear values associated with a non-meteorological artifact is shown in (c) and the histogram of its data values after hysteresis segmentation is shown in (d). Note the nearly uniform distribution of very high values.

676

677 FIG. 12. Low level (0-3 km AGL) rotation tracks associated the 27 April 2011 tornado
 678 outbreak across Mississippi and Alabama produced using different velocity dealiasing
 679 techniques, no thresholds and no MHT. (a) Tracks made using velocity dealiased with
 680 the LED algorithm. (b) Tracks made using velocity dealiased with the LED algorithm
 681 with 20-km RUC input sounding. (c) Tracks made using velocity dealiased with the Jing
 682 and Weiner (1993) technique. (d) Tracks made using velocity dealiased with the Jing and
 683 Weiner (1993) technique with 20-km RUC input sounding.

684

685 FIG. 13. Low level (0-3 km AGL) rotation tracks from the 27 April 2011 tornado
 686 outbreak. (a) Tracks created using the Jing and Weiner (1993) velocity dealiasing
 687 method with the input 20-km RUC sounding, without the azimuthal shear range
 688 correction and without the increased ReflectivityQC threshold. (b) Tracks created using
 689 the same velocity dealiasing method as in (a), but *with* the azimuthal shear range
 690 correction and the increased ReflectivityQC threshold. Note that the circled area of high
 691 azimuthal shear values associated with dealiasing errors over central Tennessee is much
 692 less prominent in (b).

693

694 FIG. 14. Low level (0-3 km AGL) rotation track from the 27 April 2011 tornado
 695 outbreak. (a) Tracks created using the Jing and Weiner (1993) velocity dealiasing
 696 method with the input 20-km RUC sounding, with range correction, increased
 697 ReflectivityQC thresholds and *without* hysteresis segmentation. (b) The same tracks as
 698 (a) but *with* hysteresis segmentation implemented.

699

700 FIG. 15. Low level (0-3 km AGL) rotation tracks across Mississippi and Alabama from
701 the 27 April 2011 tornado outbreak. (a) Tracks created using the Jing and Weiner (1993)
702 velocity dealiasing method with the input 20-km RUC sounding, *with* range correction,
703 increased ReflectivityQC thresholds, hysteresis segmentation and *without* MHT. (b) The
704 same tracks as (a) but *with* MHT. Note the several small clusters in west-central
705 Mississippi are removed.

706

707 FIG. 16. The impacts of the quality control efforts on low level (0-3 km AGL) rotation
708 track products associated with four recent tornado events: the 27 April 2011 event before
709 (a) and after (b) quality control, the 16 April 2011 event before (c) and after (d) quality
710 control, the 24 May 2011 event before (e) and after (f) quality control, and the 2 March
711 2012 event before (g) and after (h) quality control.

712

713 FIG. 17. (a) Low level (0-3 km AGL) rotation tracks over a 145-minute period associated
714 with the 24 May 2011 tornado outbreak across central Oklahoma. (b) Plotted tornado EF-
715 scale ratings associated with tornadoes that occurred during that same time period as (a).
716 Survey data provided courtesy of Kiel Ortega, Brandon Smith, and Gabe Garfield.

717

FIG. 1. Low level (0-3 km AGL) rotation tracks from the 27 April 2011 tornado outbreak. Swaths of high maximum azimuthal shear approximate the movement and strength of mesocyclone circulations within the supercells that moved southwest to northeast across the states of Alabama, Mississippi, and Tennessee between 16 UTC on 27 April and 00 UTC on 28 April.

FIG. 2. Low level (0-3 km AGL) rotation tracks across Virginia, North Carolina and South Carolina from the 16 April 2011 tornado outbreak generated using the default WSR-88D velocity dealiasing technique and without any quality control techniques. The spikes of high azimuthal shear values are caused by poor velocity dealiasing along radials and can make data interpretation difficult, if not impossible, in some areas.

FIG. 3. Radial velocity fields and the corresponding azimuthal shear fields from KDGX on 27 April 2011 at 2151 UTC created using different dealiasing strategies. (a) Radial velocity dealiased using the LED algorithm. (b) Azimuthal shear field associated with (a). (c) Radial velocity dealiased using the LED algorithm with an environmental wind field from an input 20-km RUC point sounding. (d) Azimuthal shear associated with (c). (e) Radial velocity field dealiased using the Jing and Weiner (1993) technique with an environmental wind field from an input 20-km RUC point sounding. (f) Azimuthal shear field associated with (e).

FIG. 4. Flow chart showing how rotation track products are created. Grey boxes with dashed lines represent algorithms and white boxes with solid lines represent data fields.

FIG. 5. (a) Low level (0-3 km AGL) rotation track field from the 2 March 2012 outbreak from the KVWX radar site before data removal near the radar site. Note the high values of azimuthal shear surrounding the radar site at the center of the image. (b) The same rotation track field after the removal of data within a 5-km radius of the radar site. This removal will only be performed for the climatology, not in real-time.

FIG. 6. (a) Reflectivity, (b) ReflectivityQC, (c) radial velocity, and (d) azimuthal shear fields associated with a supercell over central Alabama on 27 April 2011 at 2107 UTC.

FIG. 7. A schematic showing how hysteresis segmentation works. The first and last peaks of azimuthal shear values will be associated with clusters, while the middle peak will not be associated with a cluster because it contains no values above the higher data threshold.

FIG. 8. Low level (0-3 km AGL) rotation tracks associated with the tornadic supercells that moved across Mississippi and Alabama between 16 UTC on 27 April 2011 and 00 UTC on 28 April 2011. (a) Rotation tracks before hysteresis segmentation. (b) Rotation tracks after hysteresis segmentation is used to threshold the field.

FIG. 9. Example of how the MHT algorithm tracks clusters and generates hypotheses. Solid shapes represent the position of azimuthal shear clusters at the given time step. Solid arrows show the movement of clusters between time steps. Dotted shapes show the projected locations of the azimuthal shear clusters in the next time steps. Dashed arrows show the projected movement of the clusters between time steps. Shape A shows the projected location of the original cluster at time t . Shape B represents the actual location of the original cluster at time t . The algorithm generates two hypotheses for time $t + 1$ (C and D). If the location of B is an error, then at time $t + 1$ the cluster should move to position D. If the location of B is not an error but a change in motion, then B should move to location C at time $t + 1$. At time $t + 1$, the discovery of the target at either C or D will confirm one hypothesis and disprove the other. The disproved cluster is deleted and the confirmed one continues on to the next time step. In this case, given the strange shape and size of B, it is likely that this cluster is associated with a non-meteorological shear signature and will not persist in time $t + 1$.

FIG. 10. Multiple hypothesis tracking flow chart adapted from Root et al. (2011).

FIG. 11. An example of a cluster of high azimuthal shear values associated with a mesocyclone circulation is shown in (a) and the histogram of its data values after hysteresis segmentation is shown in (b). An example of a cluster of high azimuthal shear values associated with a non-meteorological artifact is shown in (c) and the histogram of its data values after hysteresis segmentation is shown in (d). Note the nearly uniform distribution of very high values.

FIG. 12. Low level (0-3 km AGL) rotation tracks associated the 27 April 2011 tornado outbreak across Mississippi and Alabama produced using different velocity dealiasing techniques, no thresholds and no MHT. (a) Tracks made using velocity dealiasied with the LED algorithm. (b) Tracks made using velocity dealiasied with the LED algorithm with 20-km RUC input sounding. (c) Tracks made using velocity dealiasied with the Jing and Weiner (1993) technique. (d) Tracks made using velocity dealiasied with the Jing and Weiner (1993) technique with 20-km RUC input sounding.

FIG. 13. Low level (0-3 km AGL) rotation tracks from the 27 April 2011 tornado outbreak. (a) Tracks created using the Jing and Weiner (1993) velocity dealiasing method with the input 20-km RUC sounding, without the azimuthal shear range correction and without the increased ReflectivityQC threshold. (b) Tracks created using the same velocity dealiasing method as in (a), but *with* the azimuthal shear range correction and the increased ReflectivityQC threshold. Note that the circled area of high azimuthal shear values associated with dealiasing errors over central Tennessee is much less prominent in (b).

FIG. 14. Low level (0-3 km AGL) rotation track from the 27 April 2011 tornado outbreak. (a) Tracks created using the Jing and Weiner (1993) velocity dealiasing method with the input 20-km RUC sounding, with range correction, increased ReflectivityQC thresholds and *without* hysteresis segmentation. (b) The same tracks as (a) but *with* hysteresis segmentation implemented.

FIG. 15. Low level (0-3km AGL) rotation tracks across Mississippi and Alabama from the 27 April 2011 tornado outbreak. (a) Tracks created using the Jing and Weiner (1993) velocity dealiasing method with the input 20-km RUC sounding, *with* range correction, increased ReflectivityQC thresholds, hysteresis segmentation and *without* MHT. (b) The same tracks as (a) but *with* MHT. Note the several small clusters in west-central Mississippi are removed.

FIG. 16. The impacts of the quality control efforts on low level (0-3 km AGL) rotation track products associated with four recent tornado events: the 27 April 2011 event before (a) and after (b) quality control, the 16 April 2011 event before (c) and after (d) quality control, the 24 May 2011 event before (e) and after (f) quality control, and the 2 March 2012 event before (g) and after (h) quality control.

FIG. 17. (a) Low level (0-3 km AGL) rotation tracks over a 145-minute period associated with the 24 May 2011 tornado outbreak across central Oklahoma. (b) Plotted tornado EF-scale ratings associated with tornadoes that occurred during that same time period as (a). Survey data provided courtesy of Kiel Ortega, Brandon Smith, and Gabe Garfield.